YEGOROV, N.M.; LEVINA, A.A.; VASILENOK, Yu.I.; KONOPLEV, B.A.; PARFENOVA, A.M.; KASHIRINA, N.B.

Effect of impurities in the solvent on the synthesis of low pressure polyethylene. Plast. massy. no.9:1-4 '65. (MIRA 18:9)

McNoPLEV, B. N.

Technology of motion-picture production. Mackva, Iskuestvo, 1953. 408 p. (54-22444)

TR850.K62

SOKOLOV, Ippolit Vasil'yevich; KOHOPLEV, B.N., red.; FOMIN, A.A., red.; CHICHERIE, A.E., tekhn.red.


[History of the invention of motion pictures] Istoriia izobreteniia kinematografa. Pod obshchei red. B.H.Konopleva. Moskva, Gos.izd-vo "Iskusstvo," 1960. 193 p.

(Motion pictures)


(Motion pictures)

KONOPLEV, Boris Nikolayevich; EYSYMONT, L.O., red.; REYZMAN, Ye.Ya., tekhn. red.

[Production of motion pictures]Proisvodstvo kinofil'mov. Moskva, Isd-vo "Iskusstvo," 1962. 396 p. (MIRA 16:1) (Motion pictures—Production and direction)



Kon	OPLEV,	F. C.						;
Bee	Cultur	e						·
Aci	dic fee	d supplemen	t for bees.	Pchelovods	stvo 30, No. 2,	1953.		
		•						
				\$				
							**	
9.	Month	ly List of 1	Russian Acc	essions, Lib	rary of Congress	s, June	1953, Unc	1.
						•	. •	



[The developing industry of Amur Province] Promyshlennost'
Amurskoe aknizhnoe izd-vo, 1963. 125 p.

KONOPLEV, Ivan Ivanovich; MAMONTOVA, O.K., red.

[The developing industry of Amur Province] Promyshlennost'
Amurskoe
knizhnoe izd-vo, 1963. 125 p.

(MIRA 17:4)

EWT(m)/ETC(f)/EPF(n)-2/EWG(m) IJP(c) W L 25966-66 ACC NR: AP5026440 SOURCE CODE: UR/0089/65/019/004/0350/0354 AUTHOR: Ganzha, V. D.; Yegorov, A. I.; Kaminker, D. M.; Kolyadin, Konoplev, K. A.; Saykov, Yu. P.; Sharov, V. T. ORG: none TITLE: Electrophoretic filter for reactor we'ver purification SOURCE: Atomnaya energiya, v. 19, no. 4, 1965, 350-354 TOPIC TAGS: nuclear research reactor, nuclear reactor constituen, water purification equipment, water cooled nuclear reactor, industrial false, electrophonies, corrosion, etainless steel / VVR-M nuclear reactor, IKh 18M9T stainless etael ABSTRACT: In January, 1962, a formation of turbidity in the primary loop of the VVR-M reactor of the Physicotechnical Institute im. A. F. Ioffe, AN SSSR, was observed. In June, the turbidity was so strong that a special electrophoretic filter for water purification was installed. The turbid water contained a 54-pot-suspension of hydrate aluminum oxide which was originated by the corrosion of aluminum reactor vessel and fuel-element cans. A daily amount of about 2 g/Mw of suspended particles was discharged into the water. The installed filter was equipped with the platinized titanium anodeplates, while the cathode 621.039.568 UDC: Card 1/3

L 25966-66	
ACC NR: AP5026440	7
plates were made of 1 18 9T stainless steel. A cy	Clindrical prototype of
the filter was experimentally tested and the resul	ts were explained and
graphically illustrated. The tests showed that th	e chemical composition
of turbid and filtered water was as follows:	
Turbia	Filtered
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	0
Fe+3 " " 0.4 \ SiO ₂ " " 6.0	0.18 1.3
02 " " 0.96	2.96
Optical density 0.065	0.008
The selected filter design data are summarized in	the following table.
Water flow rate in kg/hr	
Effective water flow in ou m/hr	250-500
Electrode voltage in v	0.5 110-220
Distance between electrodes in cm	1
Contact time in min. (at 250 1/hr) Total filter volume in liter	8
Interelectrode volume in liter	10.7
Electrode size in mm	7.5 170x572
Number of anode plates	4
Number of cathode plates Filter dimensions in mm	5
	400x224x935
Card 2/3	
Card 3/3 7 (2)	
	MILE STATE OF THE

L 28386-66 EPF(n)-2/EWT(m)/ETC(f)/EWG(m)/EWP(t)/ETI LJP(c) JD/JG ACC NR. AP6001792 SOURCE CODE: UR/0089/65/019/006/0517/0521 AUTHOR: Kaminker, D. M.; Konoplev, K. A.; Semenov, Yu. P.; Trenin, V. D. ORG: Physicotechnical Institute im. A. F. Ioffe of AN SSSR (Fiziko-47 tekhnical institut AN SSSR) TITLE: Reduction of radioactive discharges into the atmosphere and investigation of water deaeration conditions in the primary loop of WR-M reactor SOURCE: Atomnaya energiya, v. 19, no. 6, 1965, 517-521 TOPIC TAGS: nuclear research reactor, nuclear reactor technology, nuclear reactor component, isotope/WR-M nuclear reactor ABSTRACT: The design and the two-year operation of the closed deseration loop of the VVR-M reactor are discussed. The reactor was installed at the Physicotechnical Institute im. A. F. Ioffe. The experience with this reactor disclosed that radioactive discharges into the atmosphere from experimental holes and hot channels were unimportant in comparison with the radiolytic and gas discharges from the deaerator. It was mentioned that the Ar-41 isotope was the main product; of the bombardment of the air by neutrons. The radioactive gas discharge was reduced by using a closed deaeration system for removing and burning detonation The gas from the deaerator being preheated in a 10-kw heater was delivered to a 7-liter platinum catalyzer where a slow buring process Cord 1/2 UDC: 621.039.586:539.16.04

ROMOPLEU, K.

Category : USSR/Nuclear Physics - Structure and Properties of Nuclei

C-4

THE RESERVE OF THE PROPERTY OF

Abs Jour : Ref Zhur - Fizika, No 2, 1957 No 3200

Author : Kel'man, V.M., Metskhvarishvila, R.Ya., Romanov, V.A., Rusinov, L.I.,

Inst

: Leningrad Physicotechnical Institute, Academy of Sciences USSR Title

: Determination of the Ratios of the Internal-Conversion Coefficients for the Isomeric Transition of In 114.

Orig Pub : Dokl. AN SSSR, 1956, 107, No 3, 394-397

Abstract : A prism beta spectrometer with a transmission factor .02% and a resolution 2.04% was used to measure the ratios of the conversion coefficients at various L subshells and also at the K, M, and N shells for the 192-kev isomeric transition in Inll⁴. The ratios are L_I: L_{II}: L_{II}: (0.24 ± 0.01): (1.27 ± 0.02): 1; L/M = 4.4 ± 0.1; M/N = 4.6 ± 0.2; K/L = 1.32 ± 0.02. All data are in good agreement

with the type of multipole transition assumed (E4).

* Initials K. S. on duplicale Battelle Card.


Card : 1/1


"The work and the employment of the research reactor WWR-M with the maximum neutron flux 3.1014 n/cmf/sec."

report submitted for 3rd Intl Conf, Peaceful Uses of Atomic Energy, Geneva, 31 Aug-9 Sep 64.


GANZHA, W.D.; YEGOROV, A.I.; KAMINKER, D.M.; KOLYADIN, A.B.; KONOPLEY, K.A.; SAYKOV, Yu.P.; SHAROV, V.T.

Electrophoretic filter for purifying reactor water. Atom. energ. 19 no.4:350-354 0 65. (MIRA 18:11)





"APPROVED FOR RELEASE: 06/19/2000 CIA-RDP86-00513R000824320010-1



ACCESSION NR: AP4036534

S/0089/64/016/005/0456/0457

AUTHORS: Ganzha, V.D.; Konoplev, K.A.; Trenin, V.D.; Sharov, V.T.

TITLE: Ion exchange installation for preparing reactor feed water

SOURCE: Atomnaya energiya, v. 16, no. 5, 1964, 456-457

TOPIC TAGS: ion exchange water desalting, reactor water desalting, water desalting, reactor feed water, water cooled reactor, moderated reactor

ABSTRACT: The article describes an ion exchange water desalting installation to provide water feed for water cooled and moderated reactors. The installation has been designed at the Physical-Technical Institute im. A.F. Ioffe, An SSSR as a substitute for an unsatisfactory electric distillation plant at the VVR-M reactor, which has low capacity, rapid scale forming, and low electrical resistivity of final product). The described installation produces 3 m3/hr feed water with 1 mg/l.salt, and less than 0.02 mg/l chloride ions. The water supply is adequate for a regeneration cycle of 50 m3. Artesian water is used as feed for desalting (400 mg/l.salts, mostly Ca and Mg). Cation exchange resin KU-2 and anion exchange Cord 1/2

L 04451-67 EWT(1)

ACC NR. AP6014693 (N.A)

SOURCE CODE: UR/0105/66/000/005/0050/0054

AUTHOR: Konoplev, K. G. (Candidate of technical sciences; Sevastopol')

ORG: none

33

B

TITLE: Induction motor operating stability

SOURCE: Elektrichestvo, no. 5, 1966, 50-54

TOPIC TAGS: induction motor, induction motor skebility, electric motor, electric

ABSTRACT: Formulas are developed and curves supplied for determining the rpm variation of an induction motor upon a change of voltage applied to the motor. The moment of inertia of the drive involved, the motor braking torque, and the law of voltage variation are taken into account. The behavior of the induction motor under

the above conditions can be described by this equation: $\left[\frac{ds}{dx} + s\left[\mu + a\left(1 - e^{-x}\right)^{s}\right] = \mu$, where

$$x = \frac{t}{T} + t_0$$
; $t_0 = \ln(1 - \frac{U_0}{U_0})$; $\alpha = \frac{AT}{M_0 T_0}$; $T_{10} = \frac{GD^0 n_0}{375 M_0}$;

 $\mu = \frac{kn_0T}{M_0T_{\rm H}}$: The solution of the

20rd 1/2

UDC: 621.313.333:016.35

ACC NR. AP6014693

above equation is: $s = s_0 f_1(\alpha, x) f_2(\mu, x) + \mu f_1(\alpha, x) f_2(\mu, x) f_3(\alpha, \mu, x)$, where

 $f_1(a, x) = e^{-\phi}$; $f_2(a, \mu, x) = \int_0^x e^{\phi} dx$; $f_3(\mu, x) = e^{-\mu x}$; $\phi = \mu x + \psi$; $\psi = a(x + 2e^{-x} - 0.5e^{-ax} - 1.5)$.


The functions f_i , f_2 , and f_3 are presented in the form of curves. A special set of equations describes stability conditions. An experimental verification that included a self-excited current-compound synchronous generator, an induction motor used as a load, and a test induction motor is mentioned. Orig. art. has: 4 figures, 40 formulas, and 2 tables.

SUB CODE: 09 / SUBM DATE: 03May65 / ORIG REF: 005

Card 2/2 egh

APPROVED FOR RELEASE: 06/19/2000 CIA-RDP86-00513R000824320010-1"

2000年 · 1000年 · 1000年



Variations in the voltage of synchronous generators with different excitation systems and suddenly applied loads. Elektrichestvo no.12:

(MTRA 15:12)

46-51 D '62.

(Electric generators) (Electric power distribution)

KONOPLEV, K.G. (Sevastopol')

Measurement of the voltage of a synchronous generator with current compounding and voltage compensation during the saturation of transformers. Izv. AN SSSR. Otd. tekh. nauk. Energ. i transp. no.1:41-47 Ja-F 163.

(MIRA 16:5)

(Electric generators—Measurement) (Electric power distribution)

KONOPLEV M.

For mass participation and mastery. Voen. znan. 39 no.5: 26-27 My *63. (MIRA 16:5)

l. Nachalinik TSentralinogo strelkovo-sportivnogo kluba Dobrovolinogo obshchestva sodeystviya armii, aviatsii i flotu.
(Shooting)

- 1. KONOPLEK, N. A.
- 2. USSR (600)
- 4. Feed Grinders
- 7. How to adjust the RBB-1, 0 straw-silage cutter for chopping grass for chicken feed. Ptitsevodstve no. 8, 1952.

9. Monthly List of Russian Accessions, Library of Congress, February 1953, Unclassified.

KONOPLEY, N. A.

Konoplev, N. A.

"The effect of Various Complexes of External Factors (Temperature, Moisture, and Speed of Movement of the Air) on the Growth and Development of the Chick Embryo." Moscow Veterinary Academy, Min Higher Education USSR. Moscow, 1955. (Dissertation for the degree of Candidate in Biological Sciences)

SO: Knizhnaya letopis' No. 27, 2 July 1955

Fruit Culture	_				_				ļ
Organization of	large (commercial	orchards	on collective	e farms.,	Sad i og	g. no.	3, 1952	
							2		
. Monthly List	of Rus	sian Acces	sions, Lib	rary of Cong	ress,	May	1953.	Unclass	ified.

1. KONOPLEV. N. A.								
	1.	KON	IOPLEV.	N.	Α.			


- 2. USSR (600)
- 4. Viticulture
- 7. Successes of vineyard operators on the "Kaplanbek" State Farm. Vin. SSSR 13, 1953.

9. Monthly List of Russian Accessions, Library of Congress, April 1953, Unclassified.

- 1. KONOPLEV, N. P.
- 2. USSR (600)

"The Influence of the Thermic Conditions of Certain Currents in the Atlantic Ocean Upon the Temperature Balance of the Atmosphere". Trudy GOIN, Issue 8, 1948 (36-68)

9. Meteorologiya i Gidrologiya, No. 3, 1949, Report U-2551, 30 Oct 52.



IVANOV, V.D., dots.; POKOTILO, V.P., dots.; KONOPLEV, P.S., st. prepod.; AKSENOV, A.A., assis.; KLYKOV, K.S., assis.; MART'YANOVA, L.I., tekhn. red.


[Reference book on sawing lumber materials] Posobie po raskroiu pilovochnogo syr'ia. Arkhangel'sk, Arkhangel'ske knizhnoe izd-vo, 1962. 104 p. (MIRA 16:4)

l. Nauchno-tekhnicheskoye obshchestvo lesnoy promyshlennosti. Arkhangel'skoye oblastnoye pravleniye. 2. Kafedra lesopil'no-strogal'nykh proizvodstv Arkhangel'skogo lesotekhnicheskogo instituta (for all except Mart'yanova).

(Hardboard)

KONOPLEV, Sergey Pavlovich; MINEYEV, T.K., otv. red.

[Aluminum raw materials and the prospects of finding them in Irkutsk Province] Aliuminievoe syr'e i perspektivy ego poiskov v Irkutskoi oblasti. Irkutskoe geologicheskoe upravlenie, 1961. 67 p. (MIRA 17:3)



KONOPLEV. S. polkovník

When the fate of a man is decided. Komm. Vooruzh. Sil 46 no.10: 37-41 My '65. (MIRA 18:6)

1. Sekretar' partiynoy komissii pri politicheskom upravlenii Leningradskogo voyennogo okruga.

MEL'HIKOV, A., inzh.; KOMOPLEV, S., tekhnik

Vibrating forms for making cushion blocks for foundations. Stroitel'
(MIRA 11:11)
no.10:14 0 '58.

(Concrete construction--Formsork) (Concrete blocks)

EAT(d)/EAP(v)/EAP(k)/EAP(h)/EAP(1)34868-66

ACC NR: AF6014518

SOURCE CODE: UR/0115/65/000/011/0008/0010

AUTHOR: Orlova, M. P.; Konoplev, V. A.; Sharevskaya, D. I.; Astrov, D. N.;

Al'shin, B. I.; Medvedeva, L. A.

()RG: none

TITLE: New commercial resistance thermometer

SOURCE: Ismeritel'naya tekhnika, no. 11, 1965, 8-10

TOPIC TAGS: resistance thermometer, temperature measurement, low temperature research / PTS-100 resistance thermometer


ABSTRACT: As the PTS-100 standard platinum resistance thermometer (10-300K, ±0.01K) is suitable only for operating under laboratory conditions, two new highaccuracy designs have been developed by the authors for industrial uses. In the first design (see Figure 1), coil 1 is fastened by the glass coating of straight platinum wire 2. Four such vitrified coils constitute the sensor of the thermometer. Platinum supporting wires are used as lead-ins 4 in envelope 3 filled by

Card 1/2

VDC: 536.531

APPROVED FOR RELEASE: 06/19/2000 CIA-RDP86-00513R000824320010 0

ACC NR: AP6014518



helium through throat 5. In the second design (see Figure 2), a straight 0.1mm glass thread 2 is placed inside platinum coil 1. The latter is mounted in glass capillary 3; envelope 4 and platinum lead-ins 5 are conventional. The above designs were tested for vibration (50-3000 cps) and temperature stability (250, 100, 0C; H boiling and

Orig. art. has: 2 figures and triple points). Their thermal inertia was 5-8 sec. l table.

SUB CODE: 20, /4 / SUBM DATE: none / ORIG REF: 001 / OTH REF: 002

Fig 2

KONOPLEV, V.F.

Expand on a large scale the fruit and vegetable canning industry in the Stavropol Province. Kons.i ov.prom. 17 no.7:35 Jl 162. (MIRA 15:6)

1. Gosudarstvennyy soyusnyy proyektnyy institut po proyektirovaniyu predpriyatiy pishchevoy promyshlennosti.

(Stavropol Province—Canning industry)

KARASIK, M.Ye., insh.; KRONFEL*D, B.D., insh.; KONOPLEV, V.G., insh.; KRY-ZHANOVSKIY, V.M., insh.; ABRAGAM, S.R., insh., red.; BOBROVA, Ye.W., tekhn. red.

[Organization of construction works during the electrification of railroads; experience of the construction organizations of the Ministry of Construction for Transportation] Organizateiia stroitel—nykh rabot pri elektrifikateii shelesnykh dorog; opyt stroitel nykh organizateii Mintransstroia. Moakva, Vses. isdatel sko-poligr. ob*edinenie M-va putei soobshcheniia, 1960. 65 p. (MIRA 14:7) (Railroads—Electrification) (Railroad engineering)

KONOPLEY, V.G.

A plant with the seven-hour workday. Transp.stroi. 10 no.4: 36-37 Ap '60. (MIRA 13:9)

1. Machal'nik Kuybyshevskoy normativno-issledovatel'skoy stantsii...
(Hours of labor) (Meleuz--Precast concrete)

S/190/60/002/009/019/019 B004/B060

AUTHORS:

Patrikeyev, G. A., Gusarov, B. G., Konoplev, V. I.

TITLE:

Brittle Rupture of Polymers in High-elastic State

PERIODICAL:

Vysokomolekulyarnyye soyedineniya, 1960, Vol. 2, No. 9,

pp。1438-1439

TEXT: Polymeric material weakened by incisions is bound to undergo a brittle rupture at the incised spot at low temperatures and a certain critical elongation rate. The authors checked this assumption by a dynamometer and an MNO-2 (MPO-2) Alcop oscilloscope which allowed for elongation rates to be measured up to 2 m·sec⁻¹. In natural rubber, the tearing strength was found to be considerably reduced at an elongation rate of over 0.7 m·sec⁻¹ and temperatures of -20 ± 5°C. At this rate, a brittle rupture occurred at -60°C. Figs. 1 and 2 show the experimental data. The authors recommend the application of tearing strength tests at high elongation rates. The need is felt of an improvement in inertialess dynamometers. There are 2 figures and 2 Soviet references.

SUBMITTED:

June 11, 1960

Card 1/1

s/0078/64/009/003/0688/0692

AUTHORS: Mikheyeva, V. I.; Konoplev, V. N.

TITLE: Fusibility diagram in the dimethylformamide-sodium borohydride

system

SOURCE: Zhurnal neorg. khimii, v. 9, no. 3, 1964, 688-692

TOPIC TAGS: dimethylformamide sodium borohydride system, sodium borohydride solubility, fusibility diagram, borohydride synthesis, sodium borohydride solvate, liquidus peritectic, sodium borohydride. dimethylformamide solvate

ABSTRACT: Since sodium borohydride is the basic starting material for the synthesis of other borohydrides, its solubility in dimethylformamide (DMF) was studied to determine the possibility of using the latter in the preparation of borohydrides. The fusibility diagram was constructed for the dimethylformamide-sodium borohydride system (fig. 1). The continuous increase in liquidus temperature without a temperature maximum, in addition to breaks in the temperature of the solidus corresponding to increases in sodium borohydride content,

Card 1/3_

indicates the peritectic character of the equilibrium in the given indicates the peritectic character of the equilibrium in the given system. Three congruently melting solvates are formed: NaBH, .4DMF, from 0.66-8.9 mol.% NaBH, solutions at 8.7C, NaBH, .2DMF from 15.6 mol.% NaBH, solution at 8.7-20.4C, and NaBH, .DMF from 31.3 mol.% NaBH, at 20.4-26.5C. Above 26.5C the NaBH, is crystallized as non-solvated material. The solubility of NaBH, in DMF at 0, 25 and 50C is 5.5, 25.8 and 32.3 mol.% NaBH, (2.9, 15.3, and 19.9 wt.% NaBH,). "Optical study was conducted by V. A. Vol'nova, for which we thank her." Orig. art. has: 2 figures and 3 tables.

ASSOCIATION: Institut obshchey i neorganicheskoy khimii im. N. S. Kurnakova Akademii nauk SSSR (Institute of General and Inorganic Chemistry, Academy of Sciences SSSR)

SUBMITTED: 10Jul63

DATE ACQ: 31Mar64

ENCL: Ol

SUB CODE: CH

NR REF SOV: 007

OTHER: 010

2/3

APPROVED FOR RELEASE: 06/19/2000

CIA-RDP86-00513R000824320010-1"

"APPROVED FOR RELEASE: 06/19/2000

CIA-RDP86-00513R000824320010-1

JW/RM EWT (m) /EWP (j) /T/EWA(h) SOURCE CODE: UR/0078/65/010/009/2108/2114 10441-66 AP6000287 ACC NR AUTHOR: Mikheyeva, V.I.; Konoplev, V. N TITLE: Reaction of sodium borohydride with anhydrous magnesium chloride in N, N-dimethyl-ORG: None formamide SOURCE: Zhurnal neorganicheskoy khimii, v. 10, no. 9, 1965, 2108-2114 TOPIC TAGS: magnesium compound, sodium compound, borohydride, exchange reaction, ABSTRACT: The exchange reaction between sodium borohydride and anhydrous magnesium chloride in N, N-dimethylformamide at 25 and 50C occurs readily, forming magnesium borohydride in 87-90% yield: $MgCl_2 + 2NaBH_4 \longrightarrow Mg(BH_4)_2 + 2NaCl \downarrow$ When the solution of magnesium borohydride in dimethylformamide is kept for 48 hours at a temperature between -5 and 7C, or when the solvents ether, benzene, or diethylene glycol dimethyl ether are added, a crystal solvate of the composition Mg(BH₄)₂·6HCON(CH₃)₂⁷ separates out. The great stability of the bond between dimethylformamide and the magnesium borohydride molecule, the low thermal stability of the latter, and the low volatility of dimethyl formamide permit desolvation neither by treatment with solvents nor by vacuum distillation. UDC: 546.33'273'11+546.46'273'11


1/2 Card

	rig. art. has: 1 figure, 2 tables, and 2 formulas.	•
SUB CODE	: 07 / SUBM DATE: 17Sep64 / ORIG REF: 005 / OTH REF: 024	

IJP(c) JD/WW/JW/RM L 14215-66 ENT(n)/ENP(j)/ENA(h)/ENP(e)/ENP(b) ACC NR: AP6003641 SOURCE CODE: UR/0078/65/010/010/2363/2366 AUTHOR: Konopley, V. N.; Hikheyeva, V. I. ORG: none Solubility isotherm of magnesium borohydride and sodium boro-TITLE: hydride in N and N-dimethylformamide at 0°C Zhurnal neorganicheskoy khimii, v. 10, no. 10, 1965, 2363-2366 TOPIC TAGS: magnesium compound, sodium compound, berohydride, solubility ABSTRACT: In order to check the hypothesis that solvent molecules are occluded by Mg(BH4)2.6DMF crystals (DMF=dimethyl formamide HCON(CH3)2), the chemical nature of the phases crystallizing at 0°C in the ternary system (Mg(BH4)2-NaBH4-DHF was investigated. Equilibrium was studied by the isothermal method of solubility determination. The solubility isotherm is shown in fig. 1. It shows fields of crystallization of only three solid phases, Mg(BH4)2.6DMF, NaBH4.4DMF, and NaBH4.2DMF. The corrystallization of NaBH4.2DMF and Mg(BH4)2.6DMF has an isosmotic point at 2.32% NaBH4 and 3.11% Mg(BH4)2. The field of crystallization

UDC: 546.33'271'11+546.46'271'11

Card 1/3



DLUGACH, I.M.; KURAS, Z.F.; MURAV'YEVA, I.P.; SAMYGINA, Ye.P.; SHABAD, L.M., glav. red.; VERMEL', Ye.M., prof., zam. glav. red.; KONOPLEV, V.N., zam. glav. red.; ABELEV, G.I., red. toma; IRLIN, I.S., red. toma; SAMOYLOV, V.I., red. toma; SHABAD, L.M., red.; CONCHAROVA, T.I., tekhn. red.

[Transactions of the Eight International Cancer Research Congress in six volumes] Trudy v shesti tomakh. Moskva, Medgiz. Vol.3.[Problems in the virology and immunology of cancer. Correlations of tumor and body] Voprosy virusologii i immunologii raka. Vzaimotnosheniia opukholi i organizma. 1963. 518 p. (MIRA 17:3)

1. International Cancer Research Congress. 8th, Moscow, 1962.

2. Deystvitel'nyy chlen AMN SSSR (for Shabad).

MIKHEYEVA, V.I.; KOMOPLEV, V.N.

Reaction of sodium borohydride with anhydrous magnesium chloride
in N. N.-dimethylformanide. Zhur. neorg. khim. 10 no.9:2108-2114
S *65.

(MIRA 18:10)

GREENSTEIN, J., ed.; HADDOW, A., ed.; VASIL'YEV, Yu.M. [translator];
KONOPIEV, V.P. [translator]; SHABAD, L.M., professor, redaktor;
SIDOHOV. B.H., redaktor; DUMBRE, I.Ya., tekhnicheskiy redaktor

[Advances in cancer research. Translated from the English] Uspekhi v izuchenii raka. Perevod s angliiskogo IU.M. Vasil'eva i V.P. Konopleva. Pod red. i s predisl. L.M. Shabada. Moskva, Izd-vo inostrannoi lit-ry, Vol.2. 1956. 540 p. (MIRA 9:7)

1. Chlen-korrespondent AMN SSSR (for Shabad) (CANCER)

SHABAD, L.M., prof., glav. red.; VERMEL', Ye.M., prof., zam. glav. red.; KONOPLEV, V.P., zam. glav. red.; GEL'SHTEYN, V.I., red.; KRICHEVSKAYA, A.A., red.; SHAPOT, V.S., red.; VUL'FSON, K.G., red.; GONCHAROVA, T.I., tekhn. red.

[Transactions of the Eighth International Cancer Research Congress in six volumes] Trudy vos mogo Mezhdunarodnogo protivorakovogo kongressa v shesti tomakh. Moskva, Medgiz, 1963. Vol.2. [Problems in the biochemistry of cancer and cancerogenesis] Voprosy biokhimii raka i kantserogeneza. 586 p. Vol.4. [Problems in the biology of the cancer cell and radiobiology, radiotherapy and precancer] Voprosy biologii opukholevoi kletki i radiobiologii, luchevoi terapii i predraka. 410 p. (MIRA 17:1)

1. Mezhdunarodnyy protivorakovyy kongress, 8th. Moscow.


2. Deystvitel myy chlen AMN SSSR (for Shabad).

*

IAGOVA, N.D.; KONOPLEV, V.P. (Moskva)

Morphological changes in transplanted cancer of the mammary glands on rats after hormone therapy. Arkh. pat. 10:38-44.
162.

1. Iz laboratorii eksperimental'noy gormonoterapii (zav. - kand. biolog. nauk N.I. Lazarev) Instituta eksperimental'-noy i klinicheskoy onkologii AMN SSSR (dir. - deystvitel'nyy chlen AMN SSSR prof. N.N. Blokhin).



KONOPLEV, V.P.; LAGOVA, N.D.

Characteristics of transplantable carcinoma of the rat mammary gland. Biul. eksp. biol. i med. 50 no.7:79-81 Jl '60'. (KIRA 14:5)

1. Iz laboratorii eksperimental'noy gormonoterapii (zav. - kandidat biologicheskikh nauk N.I.Lazarev) Instituta eksperimental'noy i klinicheskoy oukologii (dir. - deystvitel'nyy chlen AMN SSSR N.N. Blokhin) AMN SSSR, Moskva. Predstavlena deystvitel'nym chlenom AMN SSSR A.D.Timofeyevskim.

(BREAST—CANCER) (CARCINOMA)

IRD, Ye.A.; KONOPLEV, V.P.

Spontaneous tumors in rats bred in the nurseries of the Academy of Medical Sciences of the U.S.S.R. Vest.AMN SSSR 17 no.11:89-96 '62. (MIRA 16:1)

1. Institut eksperimental'noy i klinicheskoy onkologii AMN SSSR. (ONCOLOGY)

SHABAD, L.M., prof., glav. red.; VERMEL', Ye.M., prof., zam. glav. red.; KONOPLEV, V.P., zam. glav. red.; MARMORSHTEYN, S.Ya., red.toma; TRAPEZNIKOV, N.N., red. toma; GONCHAROVA, T.I., tekhn. red.

[Transactions of the Eight International Cancer Research Congress in six volumes] Trudy vos mogd Mexhdunarodnogo protivoraksvege kongressa v shesti temakh. Moskva, Medgiz, Vol.5. [Problems of clinical oncology] Voprosy klinicheskoi onkologii. 1963. 462 p. (MIRA 17:3)

1. International Cancer Research Congress. 8th, Moscow, 1962.

2. Deystvitel'myy chlen AMN SSSR (for Shabad).

KONOPLEV, V.P.; LAGOVA, N.D.

Morphological changes in rat mammary cancer (RMK-1) following multiple inoculations. Biul. eksp. biol. i med. 55 no.4:91-94 Ap '63. (MIRA 17:10)

1. Iz laboratorii eksperimental'noy gormonoterapii (zav. - kand. biolog. nauk N.I. Lazarev) Instituta eksperimental'noy i klini-cheskoy onkologii (dir. - deystvitel'nyy chlen AMN SSSR N.N. Blokhin) AMN SSSR, Moskva. Predstavlena deystvitel'nym chlenom AMN SSSR L.M. Shabadom.

KONOPLEV, V.P.

Asymptotic behavior of orthonormal polynomials in unilateral singular points of weight functions (algebraic singularities). Dokl. AN SSSR 16C no.5:997-1000 F *65.

(MIRA 18:2)

1. Saratovskiy gosudarstvennyy pedagogicheskiy institut. Submitted August 4, 1964.

AUTHOR:

KONOPLEV. V.P.

20-118-1-6/58

TITLE:

On the Asymptotic Representation of the Solutions of Linear Differential Equations of Second Order (Ob asimptoticheskom predstavlenii resheniy lineynykh differentsial'nykh uravneniy vtorogo poryadka)

PERIODICAL:

Doklady Akademii Nauk, 1956, Vol 118, Nr 1, pp 25-28 (USSR)

ABSTRACT:

Let the differential equation

(1) $k(x)y^n + p(x)y^1 + [\lambda^2 g(x) + q(x)]y = 0$ $a \le x \le b$

be given. By the transformation x=x(t), y = A(t)z, c < t < dthe first derivative is eliminated :

(2) $z^n + [\lambda^2 \varphi(t) + \psi(t)]z = 0$ For (2) a "near" equation

(3) $U^* + [\lambda^2 \varphi(t) + \psi(t) + \omega(t)] U = 0$ is constructed so that $\omega(t)$ on [c,d] for great λ is small compared with $\lambda^2 \varphi + \psi$. The function $\omega(t)$ is chosen so that (3) by the transformation

 $V = \sqrt{\frac{d\xi}{d+}} U$ **\xi** = **ξ**(t)

Card 1/3

OAPPROMED: FOR RELEASE: 105/99 / 2000 Soleta PD P86-100513 R00 0 8 2 4 3 2 5 0 10 - 1 Differential Equations of Second Order

can be transformed into the form

 $V'' + 6'(\xi)V = 0 \qquad -\infty \leqslant \gamma \leqslant \xi \leqslant \xi \leqslant + \infty$ Then it is $V(\xi) = c_1V_1(\xi) + c_2V_2(\xi), \forall \{V_1, V_2\} \neq 0$ and

 $U(t) = \sqrt{\frac{dt}{d\xi}} \left[c_1 V_1(\xi(t)) + c_2 V_2(\xi(t)) \right]$. The general solution of (2) is sought in the form

 $z(t) = \sqrt{\frac{dt}{d\xi}} \left[c_1(t) V_1(\xi(t)) + c_2(t) V_2(\xi(t)) \right]$

According to the variational method one obtains for the determination of z(t) a Volterra integral equation which is solved by successive approximation. The series arising thereby is the asymptotic representation in terms of λ . The representation of x follows by retransformation.

The proposed scheme is applied to the equation:

 $x^{d}y'' + x^{d-1}p(x)y' + [\lambda^{2}x^{d+\beta}r(x) - q(x)]y = 0$, $0 \le x \le 1$

which is more complicated than those considered formerly. 3 Soviet and 11 foreign references are quoted.

Card 2/3

Polynomials orthogonal to weight functions which vanish or become infinite at some points of the orthogonality segment. Dokl. AN SSSR 141 no.4:781-784 D '61. (MIRA 14:11)

1. Saratovskiy gosudarstvennyy pedagogicheskiy institut. Predstavleno akademikan I.G. Petrovskim. (Functions, Orthogonal)

KONOPLEY, V.P.; DOROGOCHINSKIY, A.Z.; MITROFANOV, M.G.

Alkylizing toluene with propylene in the presence of aluminum chloride and polyalkyl toluenes. Trudy GrozNII no. 15:271-273

Initiating the oxidation of cymenes in the liquid phase.

Ibid.:274-277 (MIRA 17:5)

S/0181/64/006/007/2200/2202

AUTHORS: Gippius, A. A.; Vavilov, V. S.; Konoplev, V. S.

TITLE: Determination of the yield of recombination radiation connected with dislocations in germanium

SOURCE: Fizika tverdogo tela, v. 6, no. 7, 1964, 2200-2202

TOPIC TAGS: recombination emission, quantum yield, dislocation effect, lead sulfide, photoconductive device

ABSTRACT: The yield is defined here as the ratio of the number of quanta of recombination radiation to the total number of acts of recombination on the given type of centers. Since this yield must be measured when the dislocations play a predominant role in the recombination of the non-equilibrium carriers, the tested sample was bombarded with a beam of ~1 MeV electrons from a Van de Graaff accelerator. The receiver was a lead-sulfide photoresistance calibrated with

the aid of a black body. n-type germanium with electron density $n_0 \sim 5 \times 10^{14} \ \mathrm{cm}^{-3}$ and dislocation density $N \sim 10^5 \ \mathrm{cm}^{-2}$ was used. The dislocations were introduced by an abrupt change in the thermal conditions during the growth of the crystal. The tests were made at approximately 80K. The quantum yield was found to be quite small, indicating that most recombinations on the dislocations are nonradiative. Some explanations for this phenomenon are discussed. The results obtained for the quantum yield and for some related quantities are compared with data by others. "The authors thank A.' V. Spitsy*n for determining the carrier density in the sample and S. I. Vintovkin and V. V. Mikhaylov for help with the measurements."

ASSOCIATION: Fizicheskiy institut im. P. N. Lebedeva AN SSSR (Physics Institute, AN SSSR)

SUBMITTED: 24Feb64

SUB CODE: SS

NR REF SOV: 005

ENCL: 01

Other: 001

Card 2/3

ENCLOSURE: 01

Results of determination of quantum yield

<u></u>						
M ofpence	Rg-10 ⁻¹⁴ , em ⁻⁶	Ng-18-4, ou-8	f, men/em ^s .	#·10-P.	'/·10-10, cm-*·ces1	Tun. 104
4	6.5	5 {	0.5 0.75	1.7 2.5	6.2 7.7	3.7 3.1
5	5.2	4 {	0.5 1.0	1.7 3.4	3.8 6.4	2,2 1,9
7	3.8	10 {	1.25 2.25	4.2 7.4	8.2 12.8	1.9 1.7
	1 .					

1 - sample no. 2 - j (fast-electron density), microsmp/cm³, 3 = g.10⁻¹⁹ cm⁻³sec⁻¹, 4 - quantum yield, 10⁴

Card 3/3

KONOPLEV. V. V. Sovetskiye schetno-analiticheskiye mashiny. Mashiny 45-kolomnogo komplektas ms. Gosstatizdats 1954. 376 s. s ill.; 2 L. chert. 26 sm. 7.000 ekz. 17 r. 50 k. v per. [55-145]p 681.177

SO: Knizhnaya Letopsis', Vol. 1, 1956

PHASE I BOOK EXPLOITATION

1036

Ryazankin, V.N., Konoplev, V.V., and Dobetskiy, L.Y.

Sovetskiye schetno-analiticheskiye mashiny; mashiny 80-kolonnogo komplekta (Soviet Punched-card Computing Machines; Machines With 80-Columns) Moscow, Gosstatizdat, 1957. 407 p. 10,000 copies printed.

Ed.: Shentsis, Ye.M.; Tech. Ed.: Pyatakova, N.D.

PURPOSE: The monograph is a handbook for engineering and technical personnel working with punched-card computing machines. It may also be used as a textbook for students of vtuzes and vuzes specializing in computers.

COVERAGE: The authors present a detailed description of the construction of punched-card computing machines. They discuss the electric circuits and the methods for adjusting and testing the machines.

V N.Ryazankin wrote the Introduction and Chapter 4, V.V.Konoplev wrote Chapters 1 and 5, and L.Yu. Dubetskiy wrote Chapters 2 and 3.

Card 1/13

KOMOPLEY V. V.

"Review of the book "Principles of control of horned cattle sterility" #Footnote* VOLOSKOV P. A. "Princilpes of control of horned cattle sterility"

Veterinariya, Vol. 38, No. 12, December 1961, P. 71.

Calculation of the temperature mode of finned water walls. Teploenergetika 12 no.5:71-74 My '65. (MIRA 18:5)

1. Podol'skiy mashinostroitel'nyy zavod im Ordzhonikidze.

BYCHKOVSKIY, A.L., inzh.; KONOPLEV, Ye.I., inzh.; MODEL', Z.G., inzh.

Porous outer wall lining. Energomashinostroenie li no.li45-46
Ja '65.

(MIRA 38:4)

BYCHKOVSKIY, A.L. (Podol'sk); KONOPLEY, Ye.I. (Podol'sk)

Calculation of the temperature field of a tenon packing.

Izv.AN SSSR.Energ. 1 transp. no.1:135-142 Ja-F '65. (MIRA 18:4)

Toward technical progress. Metallurg 10 no.7:7 Jl 16	·3\	
l. Machalinik Byuro po ratsionalizatsii i izobretatel kuragandinskogo metallurgicheskogo zavoda.	(MIRA 18:	<i>(</i>)
		. •

"APPROVED FOR RELEASE: 06/19/2000

CIA-RDP86-00513R000824320010-1

L 01484-66 EWT(m)/EWP(w) EM

ACCESSION NR: AR5019377

UR/0124/65/000/007/V013/V013

SOURCE: Ref. zh. Mekhanika, Abs. 7V90

AUTHOR: Konopley, Yu. G.

TITLE: An experimental study of circular elastic plates subject to point loads

CITED SOURCE: Sb. Itog. Nauchn. konferentsiya Kazansk. un-ta za 1963 g. Sekts. matem., kibernet. i teoriya veroyatn., mekhan. Kazan, 1964, 134

TOPIC TAGS: elastic plate, stress analysis, stress distribution

TRANSLATION: The report describes an experimental study of circular elastic plates stressed by a point load. The following particular load conditions are discussed: 1) a point load applied at the center of the plate; 2) a point load applied at an arbitrary fixed point of the plate; 3) several point loads of equal magnitude, applied at equal intervals along the diameter of the plate; 4) a radial line load, uniformly distributed along a concentric circumference; and 5) a load uniformly distributed along the circumference of the center perforation in the plate. Boundary conditions envisioned either simple support along the external contour or rigid attachment. Strain gauge sensors are used to measure stress levels. Deflections are measured along the plate diameter by dial Cord 1/2

ACCESSIO			4.1			•				0	
indicators.	Diagra	ms are c	ompileo	i to illu esulta a	strate th	e depende ared with	nce of theore	deflection tical data	. and		
	+.	<i>Би</i> роли	-						÷		
BUB COME:	EA.			ENCL	00		•				
			N .								
							٠				
											1
	· · · · · ·								.		İ
: 				*			ن		* . * *	• .	1
								•		٠	
							÷	•			.
	. ທ					* *					
Card 2/2	P/										.

KLYKOV, Ye.V., kand.tekhn.nauk; KONOPLEV, Yu.M., insh.

Automatic braking of electric sections taking load into account. Elek.i tepl.tiaga 3 no.7:13-15 J1 '59.

(Railroads--Brakes)

(Railroads--Brakes)

KLYKOV, Ye.V., kand.tekhn.nauk; KONOPLEV, Yu.M., inzh.

Automatic regulation of the pressure of train brakes. Zhel.dor.
transp. 42 no.6:47-48 Je '60. (MIRA 13:7)
(Railroads—Brakes)

KONOPLEV, Yu.V.; KITSENKO, Yu.A.; KALICHENKO, B.V.

Using the pulse neutron-neutron logging method in studying the possibility of determining the water-oil contact in horizon 4 of the Anastasiyevka-Troitskoye oil field. Geol. nefti i gaza 9 no.4244-48 Ap *65. (MIRA 18:8)

1. Krasnodarskiy filial Vsesoyuznogo nauchno-issledovatel'skogo instituta geofizicheskikh metodov razvedki i Neftepromyslovoye upravleniye Priazovneft'.

FEDOROVA, Mina Emel'yanovna; HIGRETSKIY, Fikolay Gekarovich; RELES'KIY,
L.I., kandidat tekhnicheskikh nauk, redaktor; GUSEVA, Ie.M.,
redaktor; KUCTETA.A.I., retsentsent; HERRASOVA, O.I., tekhnicheskiy redaktor

[Technical control in cotton finishing production] Tekhnicheskii
kontrol' v khlopchatobumashnom otdelochnom proixvodstve. Moskva,
Gos. nauchno-tekhn. isd-vo Ministerstva tekstil'noi promyshl.
SSSR, 1955. 291 p. (Cotton finishing)

(MERA 9:2)

BARABANGV, L.G.; KONOPLEVA, A.I.; FODIMAN, L.V., kolorist; SHMELEVA, L.S.; CHEBIKINA, V.A., dessinator

Practices for improving the assortment and quality of production.

Tekst. prom. 21 no. 4:55-67 Ap 161. (MIRA 14:7)

l. Direktor kombinata "Trekhgornaya Mamufaktura" (for Barabanov).

2. Zaveduyushchaya otdelochnym proizvodstvom kombinata "Trekhgornaya Mamufaktura" (for Konopleva). 3. Nachal'nik laboratorii kombinata "Trekhgornaya Mamufaktura" (for Shmeleva).


(Textile fabrics)

BAYANDINA, S.A.; ISAYEVA, L.A.; TALALAYEVA, A.V.; MALYUGINA, Z.N.; KOHOPLEVA, A.V.

Clinical picture and outcome of acute disseminated lupus erythematosus. Pediatriia 37 no.1:76-83 Ja '59. (MIRA 12:1)

1. Is kliniki detskikh bolesney (dir. - deystvitel'nyy chlen AMN SSSR prof. Yu.F. Domborvskaya) i kafedry patologicheskoy anatomii (sav. - chlen-korrespondent AMN SSSR prof. A.I. Strukov) I Moskovskogo ordena Lenina meditsinskogo instituta.

(LUPUS ERYTHEMATOSUS, DISSEMIMATED, in inf. & child acute, clin. picture & outcome (Rus))



SOV/24-58-9-1/31 Dolezhil, M., Konopleva, N.K., Plaksin, I.N. and AUTHORS:

Tsibul'ka, Ya. (Moscow)

TITLE: The Effect of Various Flotation Reagents on the Interaction

Between Potassium Kanthogenate and Chalcopyrite, Pyrite and Tetrahedrite (O vliyanii flotatsionnykh reagentovregulyatorov na vzaimodeystviye ksantogenata s khal'piritom, piritom i tetraedritom)

PERIODICAL: Izvestiya Akademii Nauk SSSR, Otdeleniye Tekhnicheskikh

Nauk, 1958, Nr 9, pp 3 - 8 (ÚSSR)

ABSTRACT: Almost all the copper-bearing ores from deposits in

Western Czechoslovakia contain mainly chalcopyrite and tetrahedrite, with a small proportion of pyrite and (sometimes) pyrrhotite. Of these, tetrahedrite is of particular interest since it contains both copper and antimony, the latter element being sometimes replaced by silver and accompanied by mercury. Flotation is a convenient method for treating these ores but it produces a composite sulphide in which tetrahedrite and chalcopyrite are present in approx, equal proportion, with the result that the concentration of artimony and mercury in the concentrate is approx. 50% lower than in tetrahedrite.

Cardl/5

This comparatively low concentration of Sb and Hg

SOV/24-58-9-1/31
The Effect of Various Flotation Reagents on the Interaction Between Potassium Xanthogenate and Chalcopyrite, Pyrite and Tetrahedrite.

makes extraction of these two metals by pyrometallurgical processes more difficult and the object of the present investigation was to explore the possibilities of selective separation of tetrahedrite, chalcopyrite and pyrite by the flotation method. To this end, the effect of various factors on adsorption and desorption of potassium ethylxanthogenate (KEKH) on the investigated minerals was studied by the radicactive tracer technique. The experimental samples (97.9 - 99.36% purity, 0.06 - 0.15 mm particle size) were washed in distilled water, dried in a vacuum dessicator and stored in evacuated ampoules. The KEKH solution was prepared from solid KEKH containing the radioactive isotope s³⁵ (specific activity 315 mc/g). Two solutions were used with the concentration of KEKH equal 3.12 x 10-4 and 1.87 x 10^{-4} mol/1, corresponding to the consumption of KEKH of 300 and 180 g/t, respectively. The pH number of the solutions was adjusted by addition of HCl or NaOH and the effect of pH on the adsorption of KEKH by

SOV/24-58-9-1/31
The Effect of Various Flotation Reagents on the Interaction Between Potassium Xanthogenate and Chalcopyrite, Pyrite and Tetrahedrite

the investigated minerals was studied in the following way: 1 g of each mineral with 6 ml of the KEKH solution was stirred mechanically for 15 minutes, filtered, washed with 5 ml of distilled water and dried. The quantity of the adsorbed KEKH was determined from the radioactivity of the powder, and from the difference in the activity of the solution before and after the experiments. The results are reproduced graphically in Figure 1 (for pyrite) and Figure 2 (for tetrahedrite and chalcopyrite). In all cases the relationship between the quantity of adsorbed KEKH and pH number was quite complex with a sharp maximum at pH = 6-6.5 in the case of pyrite and at pH = 5.5-6.5 in the case of the two other minerals. In the next stage, the effect of several reagents on adsorption of KEKH was investigated by measuring the quantity of KEKH adsorbed by powdered minerals that had been previously washed in solutions containing

1 x 10⁻⁴ - 3 x 10⁻⁴ mol; of the reagents in 6 ml of the solution. The following results were obtained:

Card3/5

SOV/24-58-9-1/31

The Effect of Various Flotation Reagents on the Interaction Between Potassium Xanthogenate and Chalcopyrite, Pyrite and Tetrahedrite

Pyrite: Adsorption of KEKH decreased by: K₃Fe(CN)₆ > > K₄Fe(CN)₆ > CaO > FeSO₄ > ZnSO₄ > Na₂SO₂ > Na₂SO₃; adsorption not affected by: Na₂SO₃, NaCl, NH₄CNS; adsorption increased by: CaCl₂ < CuSO₄

Chalcopyrite: adsorption decreased by: K₄Fe(CN)₆ > CaO > Na₂So₃ > NH₄CNS; adsorption not affected by: NaCl, Na₂SO₃ > Na₂SO₄; adsorption increased by: CaCl₂ < ZnSO₄ < FeSO₄ < K₃Fe(CN)₆ < CuSO₄.

Tetrahedrite: adsorption decreased by: K₃Fe(CN)₆ > Na₂So₃; adsorption not affected by: Na₂SO₃, Na₂SO₄ > ZnSO₄ > Na₂So₃; adsorption not affected by: Na₂SO₃, Na₂SO₄, CaCl₂, NaCl, NH₄CNS; Adsorption increased by CuSO₄.

Finally, desorption of KEKH from the investigated substances by means of potassium sulphide was studied. The effectiveness of this desorbent was found to be roughly the same for all three minerals (Figure 6): with the

SOV/24-58-9-1/31

. The Effect of Various Flotation Reagents on the Interaction Between Potassium Xanthogenate and Chalcopyrite, Pyrite and Tetrahedrite

increasing concentration of Na₂S the quantity of desorbed KEKH increased, reaching 80-95% at 0.5% Na₂S.

It was concluded that selective separation of pyrite, chalcopyrite and tetrahedrite by means of adjusting the pH number of the flotation medium is not possible. The fact that adsorption of KEKH is increased by K₂Fe(CN)₆

in the case of chalcopyrite and decreased in the case of tetrahedrite could be utilised for developing a selective flotation process for these two minerals. Alternatively, a solution of Na S could be used for removing the adsorbed KEKH from all the three minerals which then could be separated by flotation using suitable activating or depressing reagents. There are 6 figures, 1 table and 3 Soviet references.

SUBMITTED: October 17, 1957

Card 5/5

ACCESSION NR: AP4012081

\$/0020/64/154/002/0310/0312

AUTHORS: Sokolik, G.A.; Konopleva, H.P.

TITLE: Design theory for compensating fields

SOURCE: AN SSSR. Doklady*, v. 154, no. 2, 1964, 310-312

TOPIC TAGS: mathematical physics, compensating field, compensating field design theory, balancing field, electromechanics, Lorentz group, Neter theorem, free field Lagiangian, Lagrangian, Abelian group

ABSTRACT: This is an attempt to find an effective form of compensating fields as coherence coefficients in a space with intrinsic degrees of freedom. The local calibration group $x' = (x) \psi$,

 $S = \exp \left[e_a \left(x \right) I_a \right]; \quad \left[I_a I_b \right] = C_{ab}^b I_c.$

is examined. Simplifying the Neter theorem for the case of a local group, we get $\mathcal{Z} = \mathcal{Z}(\psi; \nabla_i \psi), \quad \nabla_i = \partial_i - A_i^* I_a,$

 $\delta \mathcal{Z} = \frac{\partial \mathcal{Z}}{\partial \phi} \, \delta \phi + \frac{\partial \mathcal{Z}}{\partial \Psi_{A} \phi} \, \delta \nabla_{A} \phi = 0.$

(1)

Expanding & and considering Cord 1/3

 $\nabla_t \frac{\partial \mathcal{L}}{\partial \nabla_t \psi} - \frac{\partial \mathcal{L}}{\partial \psi} = 0, \quad \{\delta \partial\} = 0,$ ACCESSION NR: AP4012081

we obtain

 $\frac{\partial}{\partial x_\ell} \left(\frac{\partial \mathcal{Z}}{\partial \nabla_\ell \psi} \, I_o \psi \right) = A_\ell^c C_{cb}^a I_b^b.$

(3)

Considering the free field Lagrangian LoCA17, in which A1 enters only as a tensor,

 $F_{ik}^a = (\partial_i A_k^a - \partial_k A_i^a) - \frac{1}{2} C_{kc}^a (A_i^b A_k^c - A_k^b A_i^c),$ transforming with respect to the adjoint group of the calibration group

owing to which & retains the gauge invariance, and the uniform principle of invariance is replaced by the inhomogeneous $\partial_4 J_1^2 + f^2 = A_1^2$ call, where $f^2 = \frac{3}{3}F_{11}^{*}C_{12}^{*}C_{13}^{*}C_{$

 $A_{i}^{a} = C_{ac}^{b} \Omega_{b} \partial_{i} \Omega_{c}, \quad C_{ac}^{b'} C_{cc}^{c} \Omega_{b'} \Omega_{c'} = \delta_{cc}.$

The values n can be examined as a frame of reference defined in a space of intrinsic degrees of freedom. "In conclusion, authors wish to thank Prof. K. P. Stanyukovich for his interest in this work and valuable discussions." Orig. art. has: 6 equations.

ASSOCIATION: Nauchno-issledovatel'skiy institut elektromekhaniki (Scientific-Research Institute for Electromechanics)

ACCESSION NR: AP4012081
SUEMITTED: 31Aug63

DATE ACQ: 14Feb64 ENCL: 00
SUB CODE: MM, PH

NR REF SOV: 005

OTHER: 003

"APPROVED FOR RELEASE: 06/19/2000 CIA-RDP86-00513R000824320010-1 KONOPLEUH, N.U. MOKHOVA, T.I.; TURINYA, G.K.; KONOPLEVA, N.V. Here is a word from directors of agrochemical laboratories. Mauka i pered. op. v sel'khos. 7 no.5:33-34 My 157. 1. Argokhimicheskaya laboratoriya Petrovskoy mashinno-traktornoy stantsii, Yaroslavskoy oblasti (for Mokhova). 2. Agrokhimicheskaya laboratoriya Liyelstraupskoy mashinno-traktornoy stantsii, Latviyskoy SSR (for Turinya). 3 Agrokhimicheskaya laboratoriya Vitebskoy mashinno-traktornoy stantsii, Belorusskoy SSR (for Konopleva). (Agricultural chemistry)

KONOPLEVA, R.F. PHASE I BOOK EXPLOITATION SOV/3544

Akademiya nauk SSSR. Otdeleniye fiziko-matematicheskikh nauk

Pizika tverdogo tela; sbornik statey, II (Solid State Physics; Collection of Articles, II) Moscow, Izd-vo AN SSR, 1959. 328 p. 3,500 copies printed.

Ed.: A.F. Ioffe, Academician; Ed. of Publishing House: V. N. Filipovich; Tech. Ed.: R.A. Zamarayeva.

PURPOSE: This collection of articles is intended for physicists investigating the structures and properties of solids.

COVERAGE: This volume II of a two-volume collection of articles dealing with problems of solid state physics, was prepared by the Department of Physics and Mathematics, Academy of Sciences, USSR. The authors report on the physical properties of semiconductors such as germanium, cadmium sulfide, cadmium selanide, gallium arsenide, silicon, and various metal alloys. The electrical conductivity of these substances is studied. The effects of irradiation and acoustic phonons on semiconductors are also investigated. Several articles are

Card 1/9

Solid State Physics (Cont.)

APPROVED FOR RELEASE: 06/19/2000 CIA-RDP86-00513R000824320010

devoted to the theory of electrical breakdown. X-ray studies were made on
polycrystalline substances, and one study of the gold-barium system was carried
out. No personalities are mentioned. References accompany each article.

TABLE OF CONTENTS:

Fisher, I.Z., and Ch. K. Smolik. Temperature Dependence of Ionization Energy of Impurity Centers in a Homopolar Crystal 3

Zotov, T.D. Temperature Dependence of the Electrical Resistance of a Single Crystal of Magnetite Cooled in a Magnetic Field at a Temperature Below its Low-Temperature Transformation

Konopleva, R.F., T.V. Mashovets, and S.M. Ryvkin. Influence of Neutron Irradiation on the Recombination Process in Germanium

Kolomiyets, B.T., and T.F. Mazarova. Vitreous Semiconductors. Part V.

22

Kolomiyets, B.T., and T.N. Mamontova. Vitreous Semiconductors. Part VI

29

Campada

KONOPLEUN, E.t.

81944

The Problem of the Trapping Cross Section S/181/60/002/04/02/034 of Holes in Germanium by Defects Formed B002/B063

by Gamma Irradiation

bombardment $(3 \cdot 10^{-15} \text{cm}^2 \text{ in Ref. 1})$. There are 1 table and 7 references: 4 Soviet, 1 American, and 2 British.

ASSOCIATION: Leningradskiy fiziko-tekhnicheskiy institut AN SSSR

(Leningrad Physicotechnical Institute of the AS USSR)

SUBMITTED: October 14, 1959

Card 2/2

84083

S/181/60/002/009/024/036 B004/B056

9.4160 (1105, 1137, 1331)

AUTHORS: Ryvkin

Ryvkin, S. M., Konopleva, R. F., Maslova, L. V.,

Matveyev, O. A., Strokan, N. B., Tarkhin, D. V.,

Khozov, G. V.

TITLE:

Low-inertia Germanium Photodiodes

PERIODICAL: Fizika tverdogo tela, 1960, Vol. 2, No. 9, pp. 2199 - 2201

TEXT: Germanium photodiodes were developed in 1954 at the authors' institute; they are now being produced in industry, and have a time constant of about 10^{-5} sec. Now, the low-inertia photodiodes Φ A-M1 (FD-M1)²⁵ and Φ A-M2 (FD-M2) were developed, which have a time constant of only $(1-3)\cdot 10^{-8}$ sec. Inertia was measured by means of an apparatus schematically shown in Fig. 1. A Kerr cell fed by a Γ CC-6 (GSS-6) alternating-current generator modulated light sinusoidally with a frequency, f, of 1Mc/sec. The light, which was amplified by an Φ Y (FEU)² photomultiplier, was recorded by an CN-1 (SI-1) oscilloscope. Owing to the phase shift φ ,

Card 1/2

Low-inertia Germanium Photodiodes

84083 s/181/60/002/009/024/036 B004/B056

the oscilloscope showed an ellipse. By means of an RC phase transformer, the ellipse was changed into a straight line. From the equation tan $\varphi = 2\pi f\theta$ the time constant θ was calculated. Fig. 2a shows the function $\theta = f(R_1)$ (R_1 = load resistance). In Fig. 2b the new diodes are compared with an $\phi A = 1$ (FD-1) diode of the old type. The oscillogram shows that the new diodes precisely reproduce a A = 1 -shaped light pulse. The authors thank I. A. Lebedeva, P. I. Gorshkov, collaborators of the laboratory, and F. M. Berkovskiy, student at LGU (Leningrad State University) for their assistance. There are 3 figures and 4 references: 3 Soviet.

ASSOCIATION: Leningradskiy fiziko-tekhnicheskiy institut AN SSSR

(Leningrad Institute of Physics and Technology of the

AS USSR)

SUBMITTED:

November 6, 1959

Card 2/2

84582

54.7700 5407 any

S/181/60/002/010/003/051 B019/B070

26.1631 AUTHORS:

Zhdanovich, N. S., Konopleva, R. F., Ryvkin, S. M.

TITLE:

Annealing-out of Defects Formed by Gamma Rays in n-Type Germanium

PERIODICAL: Fizika tverdogo tela, 1960, Vol. 2, No. 10, pp. 2356-2358

TEXT: When the defects produced in n-type germanium by irradiation with frays are removed by annealing, the decrease shows a nonexponential character. For an explanation of this it is necessary to consider the diffusion of the interstitial atoms and vacancies (Refs. 2,3). Fig. 1 shows the fraction for the defects removed by annealing as a function of V t for annealing temperatures of 120, 140, and 160°C, t being the annealing time. The experimental values are seen to agree with the theory mentioned in the introduction. Similar results are obtained on bombardment by electrons and neutrons. The activation energy for the diffusion of the defects is found to be 1.01 ev. For comparison, analogous values obtained on irradiation with neutrons (1.12 ev) and with electrons (1.36 and 1.3 ev) are given (Refs. 1,3,4,5). Fig. 2 shows φ as a function

Card 1/2

84582

Annealing-out of Defects Formed by Gamma Rays in n-Type Germanium

S/181/60/002/010/003/051 B019/B070

of $Z = (4Dt/r_0^2)^{1/2}$. It is found that the experimental and theoretical values agree well for $\lambda = 0.5$ and $D_0/r_0^2 = 1.3 \cdot 10^9$ per second. r_0 is, thus, found to be $2.8 \cdot 10^{-7}$ cm, and so somewhat larger than that obtained in the case of neutron bombardment. Fig. 3 shows that by increasing the r_0 quantum flux the removal of defects by annealing is more rapid. The linear part of the curve is also reduced. In the conclusion it is stated that the theory of the removal of defects by annealing which is confined to diftusion is unable to explain some important properties which are possibly connected with the interaction of defects with other structural perturbations. There are 3 figures and 6 references: 2 Soviet and 4 US.

ASSOCIATION: Piziko-tekhnicheskiy institut AN SSSR, Leningrad (Institute of Physics and Technology of the AS USSR, Leningrad)

SUBMITTED: March 17, 1960

Card 2/2

KONOPIEVA, R.F.; RYVKIN, S.M.; YAROSHETSKIY, I.D.

Capture cross section of holes by defects formed by Y-irradiation in germanium. Fiz. tver. tela 2 no.4:566-568 Ap 160.

(MIRA 13:10)

1. Leningradskiy fiziko-tekhnicheskiy institut AN SSSR. (Germanium)

RYVKIN, S.M. & KONOPLEVA, R.F.; MASLOVA, L.V.; MATVEYEV, O.A.; STROKAN, N.B.; TAREHIN, D.V.; KHOZOV, G.V.

Germanium photodiodes with small inertia. Fiz. tver. tela 2 no.9:2199-2201 S 160. (MTRA 13:10)

1. Leningradskiy fiziko-tekhnicheskiy institut AN SSSR. (Germanium diodes)

ZHDANOVICH, N.S.; KOMOPLEVA, R.F.; RYVKIN, S.M.

Annealing of defects formed in n-type germanium by V-rays.

Fiz. tver. tela 2 no.10:2356-2358 *60. (MIRA 13:12)

1. Fiskio-tekhnicheskiy institut AN SSSR, Leningrad. (Garman rays) (Germanium)

(Semiconductors, Refect of radiation on)

3/089/61/011/006/011/014 B102/B138

WITHORS:

Konopleva, R. F., Novikov, S. R.

TITLE:

Semiconductor transmitters for measuring the relative fast neutron flux distribution in a BBP-M (VVR-M) reactor

PERIODICAL: Atomnaya energiya, v. 11, no. 6, 1961, 546 - 547

TEXT: Besides the threshold indicator method, neutron flux in the experimental channels of a reactor can also be determined by semiconductor devices. This method is based on the fact that fast neutron bombardment produces lattice defects and thus causes increased carrier concentration. The integral flux, which is proportional to the increase in conductivity (cf. Fig. 1), can be determined by measuring σ . The authors tested this method while determining the fast neutron flux in the channels of the VVR-M reactor of the Fiziko-tekhnicheskiy institut im. A. F. Ioffe AN SSSR (Physicotechnical Institute imeni A. F. Ioffe AS USSR). As neutron flux transmitters, n-type germanium samples were used (size 10·1·1 mm, resistivity 1 ohm·cm), which were placed in 0.5 mm thick cadmium containers. As the thermal-to-fast-neutron ratio was not more than 10, this

Card 1/1 2

21/11/ \$/089/61/011/006/011/014 B102/B138

Semiconductor transmitters...

Cd shield was thick enough to reduce to ~10% the thermal-neutron contribution to the change in conductivity. A constant voltage was applied to the germanium cells and the neutron flux distribution was determined from the variation in current. The method yields good results for neutron energies above 300 ev. There are 4 figures and 5 references: 4 Soviet and 1 non-Soviet. The reference to English-language publications reads as follows: Phys. Rev. 98, No. 6, 1742 (1955); Phys. Rev. 99, No. 4, 1171 (1955).

SUBMITTED: February 13, 1961

Card 2/1 2

Semiconductor transducers for measuring the relative distribution of the fast neutron flux in a VVP-M reactor. Atom. energ. 11 no.6:546-547 D '61. (MIRA 14:11) (Transducers) (Neutrons) (Nuclear reactors)